

TIKKURILA OPTIVA PRIMER

PRIMER PAINT FOR WALLS AND CEILINGS

DESCRIPTION

Waterborne acrylic primer paint for use on interior walls and ceilings. It reduces absorption of finish paint and uniform primed surface and increase efficiency for Tikkurila Optiva finish wall paints.

BENEFITS AND CHARACTERISTICS



- Decrease absorption of the surface.
- Unifies the primed surface.
- Increase coverage of topcoats from Tikkurila Optiva family
- Ecological recipe and the highest quality certification - Ecolabel.
- Recommendation Polish Society of Allergology*.
- Minimum - under the required standard - the contents of volatile organic compounds - below 1.5 g / l.

* Recommendation of the Polish Society of Allergology refers to the product after complete drying of the painted surface and airing of the room.

TECHNICAL DATA

Colours	Light shades from Tikkurila Symphony color card. Because of the specification of the product shade can be different from those in Colour Card.
Packaging	0,9 l, 2,7 l, 9 l
Gloss grade	Full matt.
Example of use	Design for painting of gypsum and carton-gypsum boards, setting cost, cement-lime plasters and concrete surfaces.
Solids content	Min. approx. 50% weight (depend on colour).
Density	approx. 1,4 g/cm ³ .
Coverage	6–8 m ² /l per with one coat. The coverage depends to a large degree on such factors as absorbability, substrate texture, application method and colour.
Drying time	At temperature +23°C, relative air humidity 50% the paint needs approx. 1 hours to dry. Application of finishing coat should be performed after min. 4 hours. In lower temperatures and higher humidity the time between the application of next coat might be longer.

TIKKURILA OPTIVA PRIMER

PRIMER PAINT FOR WALLS AND CEILINGS

APPLICATION INSTRUCTION

Application method	Brush, roller, spray (nozzle: 515, pressure: 150 bar).
Thinner	If necessary thin up to 5% with water.
Application conditions	All surfaces intended for coating must be dry, air temperature may not be lower than +5°C and not higher than +25°C, relative air humidity below 80%.
Application	Before painting stir the paint thoroughly and if necessary thin with water, up to 5%. Prime unpainted wall and ceiling surfaces with one coat of Tikkurila Optiva Primer. Application of finishing coat should be performed after min. 4 hours.
Tools cleaning	Before washing tools should be thoroughly wiped in order to remove as much paint. Clean tools with water immediately after the completion of the work.

PRODUCT SAFETY

Environmental	Do not discharge liquid rests into sewers. Empty containers and packaging containing residues of paints pass to the point for the collection of this waste. Detailed information on the possibility of collecting waste from your local Municipal Office.
Work health and safety and fire protection measures	After work and before breaks wash your hands thoroughly. If ventilation during spray application is insufficient use respirators or full face respiratory protective equipment, fitted with a filter absorbing dust P2 (II b). When painting wear appropriate protective clothing and gloves. Keep the paint out of reach of children. After application of paint in closed rooms ventilate until disappearance of smell and after that time the rooms are suitable for use. This product contains a biocidal product for the preservation of the product during storage. Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)), 1,2-benzisothiazol-3(2H)-one (BIT) and 2-methyl-2H-isothiazol-3-one (MIT). May produce an allergic reaction. Wear protective gloves. The Material Safety Data Sheet is available on Customer's request.
Storage and transport	The product must be transported and stored in containers, which protect it against influence of atmospheric conditions. The storage and transport temperature must be between +5°C and +25°C. Protect the paint against frost. Close tightly the packaging immediately after use. Tightly closed packaging should be stored in room with temperature not lower than +5°C and not higher than +25°C, protect from frost and direct sunlight
VOC	Cat. A/a. The product contains a minimal amount of volatile organic compounds below 1,5 g/l (below the applicable standard). Since 2010 permissible VOC content is less than 30 g/l.

TIKKURILA OPTIVA PRIMER

PRIMER PAINT FOR WALLS AND CEILINGS

Shelf life

3 years from production date, in factory closed packaging.

This information is not intended to be exhaustive or complete. This information is based on laboratory tests and practical experience are transferred in accordance with our best knowledge. Product quality is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we can't control the conditions under which the product is used or a variety of factors that affect the use and application of the product. We do not take responsibility for damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the information given without prior notice. "