

TIKKURILA EVERAL AQUA PRIMER

Acrylic primer for wood

PRODUCT DESCRIPTION

TIKKURILA EVERAL PRIMER – Waterborne acrylic primer for priming of interior wood and wooden like surfaces. Primer can be used on metal surfaces in dry areas that do not require corrosion protection. It is also suitable for renovation priming of previously printed surfaces with alkyd or chemically harden paints. They very well levels the base before applying the enamel topcoat. The product has a recommendation of the Polish Society of Allergy *.



* Recommendation of Polish Society of Allergy refers to the product after complete drying of the painted surface and thorough airing of the room.

TECHNICAL DATA

Colours	White and light shades from Tikkurila Symphony Colour Card, NCS.
Can size	0,9 l; 2,7 l
Base	AP.
Examples of use	The paint is designed for priming of interior wood and wood like surfaces such as: windows, doors, furniture, baseboards. It recommended also to metal surfaces in dry areas such as radiators.
Solids content	Approx. 35% vol.
Density	Approx. 1,3 kg/l.
Coverage	Up to 8 m ² /l per one coat. Actual coverage depend on many factors, such as surface texture, porosity and moisture content of the surface.
Drying time	In temperature +23°C, and relative air humidity 50% dust dry after 1, application of next coat after approx. 2 hrs. Application of the finish coat after approx. 5 hrs.

APPLICATION INSTRUCTION

Surface preparation	All surfaces should be thoroughly cleaned from dirt, dust and grease. Previously painted surfaces clean with Tikkurila Maalipesu. Rinse cleaned surface thoroughly with water and allow to dry. Remove the flaking pieces of old paint. Smooth and shiny surface should be roughened and thoroughly dusted. If necessary, level the surface with a suitable filler, and after drying sand and remove dust. Notice: Wood surfaces having knots and a tendency to yellowing resulting from the leakage of resin and other substances that cause pigmentation, protect with primer Tikkurila Multistop accordance with the instructions for use, and then apply the enamel.
----------------------------	---

TIKKURILA EVERAL AQUA PRIMER

Acrylic primer for wood

Previously painted surfaces: should be wash carefully with special agents to remove all contaminations. Rinse carefully with water and allow to dry. Remove the flaking pieces of old paint with a scraper. Hard surfaces and smooth roughened with sandpaper, then carefully remove dust.

Applicaiton method

Brush, roller, airless spray.

Conditions for airless spray:

- pressure: 140-160 bar
- nozzle: 0,013"-0,015"
- thinning: 0-5% vol.

Thinner

Water.

Application conditions

Painted surface must be dry. Painting carried out in temperature from +8°C to +25°C and relative air humidity below 80%.

Application

Before painting stir the product thoroughly. If necessary, dilute with water to 5% by volume. Apply with a brush, roller or spray. Absorbent wooden surfaces primed with primer first diluted with 5-10% vol., sanded, and then, if necessary, apply a coat of undiluted primer Tikkurila Everal Aqua Primer. In order to obtain a very smooth surface before application of enamel it is recommended to sand the primed surface with sandpaper. It is recommended to use ANZA tools.

Tools cleaning

Before washing tools should be thoroughly wiped in order to remove as much paint. Clean tools with water immediately after the completion of the work.

TIKKURILA EVERAL AQUA PRIMER

Acrylic primer for wood

PRODUCT SAFETY

Environmental

Empty containers and packaging containing residues of paints pass to the point for the collection of this waste. Detailed information on the possibility of collecting waste from your local Municipal Office.

Work health and safety and fire protection measures:

During application wear protective gloves/clothing. Contains: 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Closed spaces after application of the paint should be ventilated until the odor disappears after this time they are suitable for use.

Storage and transport

Storage and transport in tightly closed containers in temperature +5°C – +25°C in dry and ventilated areas. Protect from frost and direct sunlight.

VOC

Cat. A/g. Acceptable VOC content since 2010r. - 130 g/l.
Product contains below 130g/l of VOC.

"This information is not exhaustive and complete. The data are based on laboratory tests and practical experience are transferred in accordance with the best of our knowledge. Product quality is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we can not control the conditions under which the product is used or a variety of factors that affect the use and application of the product. We do not take responsibility for damage caused by using the product in a manner inconsistent with the recommendations and in the wrong purposes. We reserve the right to change the information given without prior notice. "