SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1 Product identifier		
Product name	: RONSEAL MULTIPURPOSE WOOD TREATMENT (MP)	
Product code	: AC001S04F501-01	
1.2 Relevant identified uses	of the substance or mixture and uses advised against	
Material uses	: Paint or paint related material.	
1.3 Details of the supplier of sheet	f the safety data	
Sherwin Williams Diversified Thorncliffe Park Chapeltown Sheffield S35 2YP	Brands Limited Not available.	
e-mail address of person responsible for this SDS	: sds@ronseal.co.uk	
1.4 Emergency telephone nu	ımber	
National advisory body/Poi	ison Centre	
Telephone number	: 111 (general public) and 0344 892 111 (Medical professional (NHS) only)	
<u>Supplier</u>		
Telephone number	: +44 (0)114 246 7171 (08:30 - 17:00)	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms

Signal word Hazard statements : Warning

: Causes serious eye irritation. Very toxic to aquatic life with long lasting effects.

Precautionary statements

RONSEAL MULTIPURPOSE WOOD TREATMENT (MP) AC001S04F501-01

SECTION 2: Hazards identification

General	:	Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	:	Wear protective clothing and eye or face protection. Wear protective gloves. Avoid release to the environment. Wash hands thoroughly after handling.
Response	:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Collect spillage.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Alcohols, C9-11, branched and linear, ethoxylated
Supplemental label elements	:	Contains 1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H- 1,2,4-triazole, permethrin (ISO), 3-iodo-2-propynyl butylcarbamate and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirement	<u>en</u>	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
Biocidal products regulation	1	
Authorisation number		: UK-2019-1194-4-0029 UK-2019-1194-5-0029

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

:

3.2 Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Тур
Alcohols, C9-11, branched and linear, ethoxylated	REACH #: , 01-2119980051-45 CAS: 68439-46-3	≤2.9	Acute Tox. 4, H302 Eye Dam. 1, H318	[1]
Propiconazole	EC: 262-104-4 CAS: 60207-90-1	≤0.3	Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
Permethrin	EC: 258-067-9 CAS: 52645-53-1 Index: 613-058-00-2	≤0.3	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=1000)	[1]
3-lodo-2-propynyl Butyl Carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10)	[1]

RONSEAL MULTIPURPOSE WOOD TREATMENT (MP) AC001S04F501-01

SECTION 3: Composition/information on ingredients

		Aquatic Chronic 1, H410 (M=1)	
REACH #:	<0.05	Acute Tox. 4, H302	[1]
EC: 220-120-9		Eye Dam. 1, H318	
CAS: 2634-33-5		Skin Sens. 1, H317	
Index: 613-088-00-6		Aquatic Acute 1, H400 (M=1)	
		Aquatic Chronic 2, H411	
		See Section 16 for the full text of the H statements declared above.	
	01-2120761540-90 EC: 220-120-9 CAS: 2634-33-5	01-2120761540-90 EC: 220-120-9 CAS: 2634-33-5	REACH #: <0.05

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	 In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole, permethrin (ISO), 3-iodo-2-propynyl butylcarbamate, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

RONSEAL MULTIPURPOSE WOOD TREATMENT (MP) AC001S04F501-01

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed		
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	
Specific treatments	: No specific treatment.	

See toxicological information (Section 11)

SECTION 5: Firefighting	jures	
5.1 Extinguishing media		
Suitable extinguishing media	commended: alcohol-resistant foam, carbon dioxide, powders.	
Unsuitable extinguishing media	not use water jet.	
5.2 Special hazards arising f	e substance or mixture	
Hazards from the substance or mixture	e will produce dense black smoke. Exposure to decomposition products muse a health hazard.	nay
Hazardous combustion products	composition products may include the following materials: carbon monoxid bon dioxide, smoke, oxides of nitrogen.	de,
5.3 Advice for firefighters		
Special protective actions for fire-fighters	ol closed containers exposed to fire with water. Do not release runoff from ins or watercourses.	n fire to
Special protective equipment for fire-fighters	e-fighters should wear positive pressure self-contained breathing apparatu CBA) and full turnout gear.	JS

SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

6.1 Personal precautions, pro	oteo	ctive equipment and emergency procedures
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	Keep unnecessary and unprotected personnel from entering. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3 Methods and material for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

AC001S04F501-01

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling	Due to the organic solvents content of the mixture:
nanumg	Prevent the creation of flammable or explosive concentrations of vapours in air an avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights at other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Information on fire and explosion protection Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
7.2 Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Notes on joint storage Keep away from: oxidising agents, strong alkalis, strong acids. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep awa from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Contaminated absorbent material may pose the same hazard as the spilt product.
7.3 Specific end use(s)	Store above 5°C (42°F) Protect from frost.
Recommendations	Not available.
Industrial sector specific solutions	Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

AC001S04F501-01

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

•		
Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
DNELs/DMELs No DNELs/DMELs available.		
<u>PNECs</u> No PNECs available		
8.2 Exposure controls		
Appropriate engineering controls	:	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
	:	Users are advised to consider national Occupational Exposure Limits or other equivalent values.
Individual protection measu	ire	<u>S</u>
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Use safety eyewear designed to protect against splash of liquids.
Skin protection		
Hand protection	:	Wear suitable gloves tested to EN374.
Gloves	:	Short term exposure less than 10 minutes Continuous use Nitrile gloves.
		Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time).
		There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be
		applied once exposure has occurred.

AC001S04F501-01

SECTION 8: Exposure controls/personal protection

	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personnel should wear protective clothing.
	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Do not allow to enter drains or watercourses.
Roforo uso of this matoria	I plaase refer to the Exposure Scenario(s) if attached for the specific and use

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

.... 41 . . _ - |-. : . - 1

0.1 Information on basic physical	a	nd chemical properties
<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	White.
Odour	:	Mild.
Odour threshold	:	Not relevant/applicable due to nature of the product.
рН	:	Not Available (Not Tested).
Melting point/freezing point	:	Not relevant/applicable due to nature of the product.
Initial boiling point and boiling range	:	100°C
Flash point	:	Closed cup: Not applicable.
Evaporation rate	:	Slower than Ether Phase
Flammability (solid, gas)	:	Not relevant/applicable due to nature of the product.
Upper/lower flammability or explosive limits	:	
Vapour pressure	:	2.3 kPa [at 20°C]
Vapour density	:	Not relevant/applicable due to nature of the product.
Relative density	:	1.01
Solubility(ies)	:	Not relevant/applicable due to nature of the product.
Solubility in water	:	Not relevant/applicable due to nature of the product.
Partition coefficient: n-octanol/ water	:	Not relevant/applicable due to nature of the product.
Auto-ignition temperature	:	Not Available (Not Tested).
Decomposition temperature	:	Not relevant/applicable due to nature of the product.
Viscosity	:	Kinematic (40°C): >0.205 cm ² /s
Explosive properties	:	Under normal conditions of storage and use, hazardous
Oxidising properties	:	Under normal conditions of storage and use, hazardous

reactions will not occur. reactions will not occur.

RONSEAL MULTIPURPOSE WOOD TREATMENT (MP) AC001S04F501-01

SECTION 9: Physical and chemical properties

9.2 Other information

Aerosol product

- 4 - 5

Heat of combustion	: 4.252 kJ/g
SECTION 10: Stability a	nd reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: No specific test data related to reactivity available for this product or its ingredients.
	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	 Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
Refer to Section 7: HANDLIN	G AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL

Refer to Section /: HANDLING AND STORAGE and Section 8: EXPOSURE C PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole, permethrin (ISO), 3-iodo-2-propynyl butylcarbamate, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Alcohols, C9-11, branched and linear, ethoxylated	LD50 Oral	Rat	1378 mg/kg	-
Propiconazole	LC50 Inhalation Vapour	Rat	1264 mg/m ³	4 hours
	LD50 Oral	Rat	1517 mg/kg	-
Permethrin	LD50 Dermal	Rat	1750 mg/kg	-
	LD50 Oral	Rat	383 mg/kg	-
3-lodo-2-propynyl Butyl Carbamate	LD50 Oral	Rat	1470 mg/kg	-
1,2-Benzisothiazolone	LD50 Oral	Rat	1020 mg/kg	-

Acute toxicity estimates

RONSEAL MULTIPURPOSE WOOD TREATMENT (MP)

AC001S04F501-01

SECTION 11: Toxicological information

Route	ATE value
Oral	68900.07 mg/kg
Inhalation (vapours)	1185.77 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Permethrin	Skin - Mild irritant	Rabbit		24 hours 500 milligrams	-
1,2-Benzisothiazolone	Skin - Mild irritant	Human		48 hours 5 Percent	-

Conclusion/Summary	: Not available.

Sensitisation

Conclusion/Summary : Not available.

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
3-Iodo-2-propynyl Butyl Carbamate	Category 1	Not determined	larynx

Aspiration hazard

No data available

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
Alcohols, C9-11, branched and linear, ethoxylated	Acute EC50 5.36 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute EC50 2686 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8500 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Propiconazole	Acute EC50 1.29 mg/l Fresh water	Algae - Chlorella vulgaris	96 hours
	Acute EC50 3.2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute IC50 390 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute LC50 0.763 mg/l Marine water	Crustaceans - Palaemon	48 hours
ate of issue/Date of revision	21, Jun, 2019. Date of previous issue	: No previous validation. Version :	1 9/

RONSEAL MULTIPURPOSE WOOD TREATMENT (MP)
AC001S04F501-01

SECTION 12: Ecological information

J			
		adspersus - Juvenile (Fledgling, Hatchling, Weanling)	
	Acute LC50 0.85 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic IC10 6.8 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0.31 ppm Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.18 µg/l Fresh water	Fish - Oncorhynchus mykiss	30 days
Permethrin	Acute EC50 68 µg/l Marine water	Algae - Skeletonema costatum - Exponential growth phase	96 hours
	Acute EC50 0.11 µg/l Fresh water	Crustaceans - Orconectes immunis	48 hours
	Acute EC50 0.112 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.62 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.66 µg/l Fresh water	Fish - Pimephales promelas - Embryo	32 days
3-lodo-2-propynyl Butyl Carbamate	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours
	Acute LC50 40 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 67 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days
1,2-Benzisothiazolone	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours

12.2 Persistence and degradability

Conclusion/Summary	: Not available.
--------------------	------------------

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

PBT	: Not applicable.
vPvB	: Not applicable.

12.6 Other adverse effects	:	No known significant effects or critical hazards.
	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13: Disposal considerations

13.1 Waste treatment met	hods	
<u>Product</u>		
Methods of disposal	Disposal of t with the requ and any regi recyclable p disposed of	tion of waste should be avoided or minimised wherever possible. this product, solutions and any by-products should at all times comply uirements of environmental protection and waste disposal legislation jonal local authority requirements. Dispose of surplus and non- products via a licensed waste disposal contractor. Waste should not be untreated to the sewer unless fully compliant with the requirements of es with jurisdiction.
Date of issue/Date of revision	: 21, Jun, 2019.	Date of previous issue : No previous validation. Version : 1 10/14

Date of issue/Date of revision	: 21, Jun, 2019.	Date of previous issue	: No previous validation.	Version	:1	10/
--------------------------------	------------------	------------------------	---------------------------	---------	----	-----

RONSEAL MULTIPURPOSE WOOD TREATMENT (MP) AC001S04F501-01

SECTION 13: Disposal considerations

Hazardous waste	: Yes.
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations.
	If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.
	For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
03 02 02*	organochlorinated wood preservatives	
Packaging		
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.	
European waste catalogue (EWC)	 Recycling possible. Ensure packaging is completely empty before recycling. Dispose of uncured residues in the same way as the product itself. Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06. 15 01 10* packaging containing residues of or contaminated by hazardous substances 	
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

	ADR/RID	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propiconazole)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alcohols, C9-11, branched and linear, ethoxylated). Marine pollutant (Alcohols, C9-11, branched and linear, ethoxylated)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alcohols, C9-11, branched and linear, ethoxylated)
14.3 Transport Hazard Class(es)/ Label(s)	9	9	9
14.4 Packing group	111	111	111
14.5 Environmental hazards	Yes.	Yes.	Yes.
Date of issue/Date of rev	rision : 21, Jun, 2019. [Date of previous issue : No previous v	validation. Version :1 11

AC001S04F501-01

SECTION 14: Transport information

Additional	This product is not regulated	This product is not regulated	This product is not regulated
information	as a dangerous good when	as a dangerous good when	as a dangerous good when
	transported in sizes of ≤5 L or	transported in sizes of ≤5 L or	transported in sizes of ≤5 L or
	l ≤5 kg, provided the	≤5 kg, provided the	≤5 kg, provided the
	packagings meet the general	packagings meet the general	packagings meet the general
	provisions of 4.1.1.1, 4.1.1.2	provisions of 4.1.1.1, 4.1.1.2	provisions of 5.0.2.4.1,
	and 4.1.1.4 to 4.1.1.8.	and 4.1.1.4 to 4.1.1.8.	5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in user the event of an accident or spillage.

14.7 Transport in bulk : Not applicable. according to Annex II of Marpol and the IBC Code

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions : Not applicable. on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles **Other EU regulations**

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.			
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number 		
	vPvB = Very Persistent and Very Bioaccumulative		

AC001S04F501-01

SECTION 16: Other information

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classi	fication Justification
Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	Calculation method Calculation method Calculation method
Full text of abbreviated H statements	 H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H372 Causes damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	 Acute Tox. 3, H331 Acute Tox. 4, H302 Acute Tox. 4, H302 Acute Tox. 4, H332 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 2, H411 Aquatic Chronic 2, H411 Eye Dam. 1, H318 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT RE 1, H372 Acute Tox XICITY (inhalation) - Category 1 ACUTE TOXICITY (inhalation) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 Skin Sens. 1, H317 STOT RE 1, H372 Acute ToxiCITY (inhalation) - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
Date of printing	: 21, Jun, 2019.
Date of issue/ Date of revision	: 21, Jun, 2019.
Date of previous issue	: No previous validation.
	 If there is no previous validation date please contact your supplier for more information.
Version	: 1
Notice to reader	

AC001S04F501-01

SECTION 16: Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country or local laws. The conditions for use of the product are not under the control of the manufacturer, therefore the customer/buyer/ user is responsible for determining the conditions necessary for the safe use of this product. The customer/ buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

14/14