



Technical Data Sheet

Blackfriar Aluminium Wood Primer

An aluminium primer for hardwoods. Specifically formulated for painting new or old bare hard or resinous woods.

Performance characteristics –

- Contains aluminium pigments to protect against bleed from resinous woods.
- For resinous and bare hard woods.
- Good barrier properties.
- Interior and exterior use.

Preparation - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Treat knots and resinous areas with Blackfriar Patent Knotting and allow to dry before applying Blackfriar Aluminium Wood Primer.

Application - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, short pile roller or spray. Apply a generous even coat and brush well into the grain. Apply one or two coats as required.

Thinning - Maximum 5% white spirit.

Limitations - Do not use under cold (less than 5°C), damp or humid conditions. Oily hardwoods such as Teak or Iroko must be fully degreased with white spirit or methylated spirits prior to application of this product. Failure to do this may result in extended drying times and/or adhesion failure.

Coverage - Up to 14m² per litre per coat.

Drying Time - Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Remove as much product as possible from

application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning

Flammable liquid and vapour.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Store in a well-ventilated place. Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: 2-butanone oxime. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 450g/l (2007) 350g/l (2010.) This product contains a maximum of 350g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.