



Technical Data Sheet

Blackfriar Exterior Varnish

Enhances and protects all wood and external joinery. **Blackfriar Exterior Varnish** provides protection to all types of wood by resisting UV light to give your wood superior durability when applied over Blackfriar UV Wood Primer.

Performance characteristics –

- Enriches and protects your home and garden wood.
- Superior durability when applied over Blackfriar UV Wood Primer.
- Tough and flexible.
- Absorbs ultra violet light.
- Weather resistant.
- For use on bare or stripped wood.

Preparation - Timber must be clean, dry, smooth and free from any surface contamination such as oils, grease, loose or flaking varnish and denatured timber that may affect the performance of the Blackfriar Exterior Varnish. Remove excess resin from knots and clean with methylated spirit. Due to its orange/brown colour Blackfriar Patent Knotting should not be used under the Blackfriar Exterior Varnish. Oily woods, such as teak or iroko, should be thoroughly cleaned with a cloth impregnated with white spirit to remove natural oils. Non-ferrous nails are recommended for fixing beading etc. Remove old varnish completely with Blackfriar Professional Paint and Varnish Remover, and then treat as new timber: Any French Polishes must also be completely removed.

Application - Apply 2 coats of Blackfriar UV Wood Primer by brush. Followed by 2 coats of Blackfriar Exterior Varnish for maximum durability. Work Blackfriar Exterior Wood Varnish into all areas of detail and joints. Allow to dry fully between coats. Do not apply the system to damp wood as this will limit penetration and affect durability.

Coverage - 12-14m² Litre per coat. 2 coats are essential. Always apply over Blackfriar UV Wood Primer.

Drying time - Touch Dry 4-6 hours at 10°C. Overcoat after 16 hours at 10°C.

Limitations - As with all exterior grade varnishes, inspect the coating regularly and maintain immediately if any sign of breakdown occurs. A maintenance coat is recommended at least annually, may be more frequent on areas subject to high UV levels.

Clean up - Remove as much product as possible from application equipment before washing with white spirits. Do not empty product into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

Warning

Contains: Naptha (petroleum), hydrotreated heavy.

Flammable liquid and vapour. May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour. Avoid release to the environment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Call a doctor if you feel unwell.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, neodecanoic acid, cobalt salt and 2-butanone oxime.

May cause an allergic reaction. Repeated exposure may cause skin dryness or cracking.

EU limit values for this product: (Cat IIA/e): 500g/l (2007) 400g/l (2010.) This product contains a maximum of 400g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.