



# Technical Data Sheet

## Blackfriar High Gloss Paint

**Blackfriar High Gloss Paint** is specially formulated to provide a hard-wearing finish with increased flexibility meaning it lasts longer than ordinary gloss paints. It is ideal for wood, metal, plaster and most paintable interior and exterior surfaces.

### Performance characteristics –

- High gloss finish.
- Interior and exterior use.
- For metal, wood, plaster and more.
- Hard-wearing.

**Preparation** - Ensure the surface to be painted is clean, dry, and free from any rust, oils, wax or any other surface contamination. Remove any loose or flaking paint back to a firm edge, abrade any existing coating to provide a key. Rusty metals should be wire-brushed to a clean bright surface and primed immediately with Blackfriar Quick Drying Anti-Rust Primer. Galvanized metal should be degreased and primed with Blackfriar Multi-Surface Primer. New and bare surfaces should be primed with an appropriate primer such as Blackfriar Multi-Surface Primer.

**Application** - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, roller or spray. Two coats are recommended to give best protection.

**Thinning** - Not recommended.

**Limitations** - Do not use under cold (less than 5°C), damp or humid conditions. Blackfriar High Gloss Paint is not resistant to petrol or fuel oil (use Blackfriar Quick Drying Metal Paint). Not suitable for direct application to galvanised metal, use Blackfriar Multi Surface Primer first.

**Coverage** - Up to 14m<sup>2</sup> per litre per coat.

**Drying Time** - Touch dry in 4-6 hours. Recoat after 16 hours and within 3 days. Drying times are based on an

ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

**Clean Up** - Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Storage** - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

### Warning

**Contains: Naphtha (petroleum), hydrotreated heavy.**

Flammable liquid and vapour. May cause drowsiness or dizziness. Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Avoid breathing vapour.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Call a doctor if you feel unwell.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: Ethyl methyl ketoxime. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking.

EU limit values: 600g/l (2007) 300g/l (2010.) This product contains a maximum of 300 g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.