



Technical Data Sheet

Blackfriar High Performance Undercoat

A high build undercoat with good obliterating properties. Suitable for use as an 'intermediate coat' between primer and finishing coats on most common substrates. Ideal for wood, plaster and metal. A slightly structured coating with good leveling and covering properties.

Performance characteristics –

- Excellent obliteration.
- Ideal foundation for finished coat.
- Interior and exterior use.
- Ideal for wood, metal and plaster.

Preparation - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Previously painted surfaces in sound condition should be abraded and degreased prior to application of Blackfriar Undercoat. Remove any rust and abrade back to a clean bright surface before priming with Blackfriar Anti-Rust Primer. New or other bare surfaces should be primed with the appropriate Blackfriar primer followed by a coat of Blackfriar Undercoat.

Application - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, roller or spray.

Thinning - Not recommended.

Limitations - Do not use under cold (less than 5°C), damp or humid conditions. Ensure knots are sealed with Blackfriar Patent Knotting Solution.

Coverage - Up to 14m² per litre per coat.

Drying Time - Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Remove as much product as possible from

application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning.

Flammable liquid and vapour.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Store in a well-ventilated place. Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: Neodecanoic acid, cobalt salt and 2-butanone oxime. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 400g/l (2007) 300g/l (2010.) This product contains a maximum of 300g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.