



# Technical Data Sheet

## Blackfriar Patent Knotting

**Blackfriar Patent Knotting** solution seals and prevents seepage from knots and resinous areas on timber. For use on interior and exterior bare or stripped wood.

### Performance characteristics –

- Interior and exterior use.
- Seals knots.
- Prevents seepage.
- Translucent amber solution.
- Use only under opaque coatings.
- 

**Preparation** - Ensure surface is clean, dry and dust free. Remove any excess resin from knots by scraping then cleaning with methylated spirit.

**Application** - Ensure the product is thoroughly shaken prior to use. Apply evenly using a soft brush. Overlap the knot or resinous area by at least 12mm. Apply a minimum of 2 coats, allowing to fully dry between coats.

**Thinning** - Not required.

**Limitations** - Not to be used as a finishing coat. Not suitable for use under clear coatings. If knots exude excess resin we recommend that they are completely removed and made good with sound timber and wood filler or a wood stopper.

**Drying Time** - Touch dry in 15 - 30 minutes. Recoat after 1 hour. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

**Clean Up** - Remove as much product as possible from application equipment before washing with methylated spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of

waste coatings.

**Storage** - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

### Danger

#### Contains: Methanol.

Highly flammable liquid and vapour.

May cause damage to organs.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Do not breathe vapour.

In case of fire: Use water spray, dry chemical powder or carbon dioxide to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

EU limit values: 700g/l (2007) 700g/l (2010.) This product contains a maximum of 700g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.