



Technical Data Sheet

Blackfriar Quick Drying Floor Varnish

This varnish has been specially formulated to protect the floors in your home with an attractive, long-lasting scratch-resistant finish. The satin finish provides additional slip-resistance. The varnish dries quickly so you could transform your floors in just one day. Easy to clean and perfect for all wooden flooring.

Performance characteristics –

- For all interior wooden doors.
- Scratch and slip-resistant finish.
- Quick drying - touch dry in just 60 minutes.
- Non yellowing.
- Easy to clean.

Preparation - Ensure surface to be varnished is clean, dry, sound and free from wax, oil or any other contamination. If wax has been used clean the surface thoroughly with white spirit prior to sanding. Bare wood should be sanded to a smooth surface, always working with the grain. Sound, previously varnished surfaces should be lightly sanded to provide a key. Existing varnished surfaces which are unsound or in poor condition can be stripped back to bare timber with Blackfriar Professional Paint and Varnish Remover.

Application - Stir thoroughly prior to use. The product may be applied by brush or roller. If applying by brush, apply evenly using light strokes following the grain of the wood. If rolling, use a short nap mohair roller. For best results 3 coats are recommended on new wood and 2 coats on previously varnished surfaces. Prior to application of the final coat or if the overcoating time is exceeded lightly abrade with fine glass paper working with the grain and remove dust. The varnish will appear cloudy when wet but will quickly dry to a clear finish. When applying to new or bare wood, thin the first coat with up to 10% water.

Limitations - Not suitable for use on plastic type materials, eg. imitation wood. If applying varnish to cork tiles, pre-finished tiles or laminate flooring we recommend a trial

application on an inconspicuous area of the floor. Once dried check adhesion by scratching firmly with a finger nail. New concrete should be allowed to dry for at least 6 months before varnishing. Do not use under cold (less than 10°C), damp or humid conditions. Do not wash the varnished surface for at least 3 days after application. If water is spilled on it during this period gently wipe off with a soft dry cloth.

Coverage - Up to 14m² per litre per coat.

Drying Time - Touch dry in 1 hour. Recoat after 4 hours and within 3 days. Drying times are based on ambient temperature of 20°C and 50% humidity. Lower temperatures and higher humidity levels will prolong drying and overcoating times.

Clean Up - Remove as much paint as possible from equipment before cleaning. Clean with warm water, rinse and dry thoroughly.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Safety data sheet available on request.

EU limit values: 140g/l (2007) 140g/l (2010.) This product contains a maximum of 140g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.