



Technical Data Sheet

Blackfriar Quick Drying Metal Paint

Specially formulated to provide a tough, long-lasting, high-gloss finish, **Blackfriar Quick Drying Metal Paint** is ideal for interior and exterior use for factory maintenance (such as plant and machinery) as well as around the home on vehicles, bicycles, signs, garden furniture, gates railings, garage doors etc.

Performance characteristics –

- Interior and exterior use.
- For metal and wood.
- Hardwearing.
- Heat resistant to 150°C/ 300°F.
- Resists fuels, oils and grease.

Preparation - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Previously painted surfaces in sound condition should be abraded and degreased prior to direct application of Blackfriar Quick Drying Metal Paint. Remove any rust and abrade back to a clean bright surface before priming with Blackfriar Anti-Rust Primer. New or other bare surfaces should be primed with the appropriate Blackfriar Primer. No undercoat is necessary. Galvanised metal should be degreased and primed with Blackfriar Multi-Surface Primer.

Application - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, roller or spray. Two coats are recommended to give best protection.

Thinning - Not recommended.

Limitations - Do not use under cold (less than 5°C), damp or humid conditions. For full fuel / oil resistance allow to dry for at least 3 days before use. Blackfriar Quick Drying Metal Paint in Silver is not resistant to petrol, fuel oil or brake fluid. Not suitable for direct application to galvanised metal, use Blackfriar Multi-Surface Primer first.

Coverage - Up to 14m² per litre per coat.

Drying Time - Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning

Contains: Naphtha (petroleum), hydrotreated heavy. Flammable liquid and vapour. May cause drowsiness or dizziness.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour or spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Call a doctor if you feel unwell.

Store in a well-ventilated place. Store locked up.

Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: Neodecanoic acid, cobalt salt and 2-butanone oxime. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 600g/l (2007) 500g/l (2010.) This product

contains a maximum of 500g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.