



Technical Data Sheet

Blackfriar Wood Primer

A high performance solvent based primer for new or old bare soft wood. Penetrates the surface of the wood to provide an excellent foundation for painting.

Performance characteristics –

- For bare soft wood.
- Excellent adhesion.
- Flexible.
- For interior and exterior use.

Preparation - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Treat knots and resinous areas with Blackfriar Patent Knotting and allow to dry before applying Blackfriar Wood Primer.

Application - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, short pile roller or spray. Apply a generous even coat and brush well into the grain. Apply one or two coats as required.

Thinning - Thinning not recommended.

Limitations - Do not use under cold (less than 5°C), damp or humid conditions. Not recommended for hardwoods or resinous woods (use Blackfriar Aluminium Wood Primer).

Coverage - Up to 14m² per litre per coat.

Drying Time - Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning

Flammable liquid and vapour.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Store in a well-ventilated place. Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains neodecanoic acid, cobalt salt. May produce an allergic reaction.

EU limit values: 450g/l (2007) 350g/l (2010.)

This product contains a maximum of 350g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.