



Premium Masking Solutions

3560 Q1® Precision Line Masking Tape

3560 Q1® Precision Line Masking Tape is an ultra-thin paper masking tape for perfect razor sharp paint edges. This professional high-performance fine line masking tape is ideal for precise high-quality spray painting jobs in indoor and outdoor, and can be easily applied and removed. It sticks well on smooth surfaces and it is compatible with both solvent-based and water-based paints. 3560 Q1® Precision Line Masking Tape guarantees perfect adhesion and assures easy and clean removal without leaving any kind of residue on the application surface, nor peeling of the substrate. It is engineered for HVLP and airless paint spray, and is UV and water resistant.



Features & Benefits

- Ultra-thin paper for razor sharp paint edge
- 6 months indoor clean removal
- 3 months UV & Water Resistant
- Fast application with minimal stretching from the roll
- Compatible with solvent and water-based paints

Available Colour

Yellow

Product Reference

Part#	Size	Pcs/ Case
PPL125	25 mm x 50 m	36 rolls/ case
PPL138	38 mm x 50 m	24 rolls/ case
PPL150	50 mm x 50 m	20 rolls/ case

Backing Material

Washi Paper

Type of Adhesive

Water base acrylic

Technical Data Sheet

Characteristics	Metric	Imperial Units	Test method
Total Weight	82 g/m ²	82 g/m ²	ISO 536
Total Thickness	92 µm	3.6 mils	Internal Method
MD tensile strength	30 N/cm	17.1 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break	3.5%	3.5%	AFERA 5004/PSTC 131
Adhesion to steel plate	1.4 N/cm	12.8 oz/in	AFERA 5001/PSTC 101
UV light resistance	340 hours	340 hours	Atlas Suntest XLS+ (II)



Additional Information**Storage & Handling**

Q1® Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1® Premium Masking Solutions does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Product Use

Q1® would advise that there are many factors beyond Q1® control but within the users knowledge that can affect the use and performance of Q1® products. Q1® remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® literature.