

Expert finishes for wood and metal

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

March 2018

PRODUCT DATA SHEET

Product	Quick Dry All Surface All Purpose Paint				
Туре	A high performance acrylic satin paint available in black, white, cream, oxford blue and green.				
Intended Use	For use on a wide range of surfaces such as UPVC, most plastics, timber, metal, tiles, stone and bricks without the need of a primer.				
Special Features	Quick drying and easy to apply to on an extensive range of surfaces both indoors and outdoors.				
Preparation	The surface must be clean and free from dust and any loose paint, wax, grease, dirt, fungal growth or solid matter likely to interfere with the adhesion of the paint. Do not apply to damp areas. Sources of damp should be eliminated before applying the paint. The product can be applied to surfaces without the need of a primer. However on metal improved protection will be achieved if an anti-corrosive metal primer such as Rustins Quick Dry Red Oxide Primer or Rustins Galvanised Primer is first applied. The product can also be applied directly to timber but a suitable primer such as Rustins Quick Dry Primer and Undercoat will help to reduce the appearance of the grain of the timber if this is important.				
Application	STIR WELL BEFORE USE. Do not thin the product. Apply evenly by brush. One or two coats should be applied allowing 3-4 hours between coats in warm dry conditions. Cold damp conditions will significantly extend the drying times. Do not apply outdoors when foggy or likely to rain before the paint has dried.				
Coats	1 coat is usually sufficient. A second coat may be applied for improved durability.				
Drying Time	Approximately 30 minutes, depending on temperature and humidity.				
Re-coating Time	Approximately 3-4 hours				
Application Temp.	Ideally 15-25°C. Do not apply if rain imminent.				
Coverage	12-14 sq.metres per litre 1 coat.				
Maintenance	The surface may be washed with a mild detergent solution and a scrubbing brush and recoated if necessary.				
Compatibility	May be applied to a wide range of surfaces and paints but test for compatibility and adhesion if in doubt.				
Settlement	STIR WELL BEFORE AND DURING USE.				
Shelf-life/Storage	Many years if stored in original tightly closed container in a cool dry place.				
Hazards	Keep out of reach of children. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. A full Safet Data Sheet is available upon request or on Rustins Web site.				
Clean-Up	Remove excess product from brushes before cleaning. Clean brushes whilst wet with water. Hard brushes can be cleaned with Rustin's Brush Restorer.				
Sizes	250ml 500ml 1 litre				