

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Chalky Finish Paint</b>
<b>Type</b>	Formulated with water borne acrylic emulsion, pigments and extenders to provide excellent opacity and a smooth chalky surface feel. Available in matt white and pastel shades.
<b>Intended Use</b>	For use on bare wood, hardboard, MDF, plaster, brickwork and cement to produce a smooth touch flat matt finish. (Not for direct application to metals). Can also be used as a finish coat over existing wood and metal primers and paints. For interior use.
<b>Special Features</b>	Quick drying. Low odour. Wash application equipment in water. Excellent covering power. One coat is usually sufficient to completely cover previously painted surfaces giving a smooth chalky matt finish to an article. Priming and sanding may not be necessary on some substrates.
<b>Preparation</b>	Surfaces to be coated must be clean, dry and free from wax, grease and contaminants. When used to prime bare wood, knots must be sealed with <b>Rustins Knotting</b> . Fill holes and cracks with <b>Rustins Wood Filler</b> after priming. .
<b>Application</b>	Apply liberally and evenly with a synthetic short fibre brush or roller. For brush application, the primer coat may be thinned by mixing 5 parts with 1 part water if necessary.
<b>Coats</b>	One coat over primed surfaces. A minimum of 2 coats are required on bare substrates.
<b>Drying Time</b>	Touch dry within 30 minutes, depending on temperature and humidity.
<b>Re-coating Time</b>	2 hours minimum, depending on temperature and humidity.
<b>Application Temp.</b>	Ideally 15-25°C. Do not use below 10°C or in conditions of high humidity.
<b>Coverage</b>	Approximately 13 sq.m per litre, 1 coat, depending on the absorbency of the surface.
<b>Maintenance</b>	Wash with damp cloth.
<b>Compatibility</b>	Compatible with many paint products, May be tinted with water-borne tinting bases, but must be tested for compatibility first. Not for use as a metal primer. Metals must be primed using <b>Rustins Red Oxide Metal Primer</b> . Not a stain-blocking product. If unsure, test on a small inconspicuous area before proceeding.
<b>Settlement</b>	<b>STIR WELL BEFORE USE.</b> Ensure any sediment is thoroughly mixed in.
<b>Shelf-life/Storage</b>	Many years in a cool, dry place if stored in original, tightly closed container. Do not store below 5°C. Protect from frost and extremes of temperature.
<b>Hazards</b>	Non-flammable. Avoid contact with eyes and skin. Eyes and skin should be rinsed immediately if contact occurs with plenty of water. Seek medical attention. Keep container tightly closed and out of reach of children. A full Health and Safety Data Sheet is Available on request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	Clean brushes and hands immediately after use with water. If dried on, clean equipment and brushes with <b>Rustins Brush Restorer</b> .
<b>Sizes</b>	250 ml, 500 ml.