

Expert finishes for wood and metal

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

March 2018

PRODUCT DATA SHEET

March 2018	TRODUCT DATA SHELT
Product	Quick Dry Masonry Paint
Туре	A high quality acrylic matt masonry paint available in black, white, red and cream.
Intended Use	For use on sound, dry exterior masonry surfaces.
Special Features	Quick drying and formulated for ease of application and good exterior durability.
Preparation	Surfaces must be sound, clean, dry and free from dust, dirt and contaminants likely to affect adhesion. Remove any existing finish, which may be flaking and remove any loose particles and mortar. Fill cracks and repair damaged pointing. Surfaces showing signs of efflorescence (white crystals on the surface) should be brushed down and a coat of Alkaliresisting Primer must then be applied and allowed to dry before applying Rustins Masonry Paint. No Primer is required if fresh mortar has been applied to the pointing and if painting new brick work. If applying to existing painted surfaces test for compatibility as if not compatible it may flake off. Do not apply to areas where there is persistent damp.
Application	Use a large brush and apply evenly. Apply paint liberally, making sure the surface is covered completely. Do not apply when temperatures are below 10 C, in conditions of high humidity or when there is a risk of rain.
Coats	1 coat is usually sufficient. A second coat may be applied if required.
Drying Time	Approximately 30 minutes, depending on temperature and humidity.
Re-coating Time	Approximately 4 hours depending on ambient conditions.
Application Temp.	Ideally 15-25°C. Do not apply if rain imminent.
Coverage	14 sq.metres per litre 1 coat.
Maintenance	The surface may be washed with a mild detergent solution and a scrubbing brush and recoated if necessary.
Compatibility	May be applied over other paints but test for compatibility as the paint may flake off if not compatible.
Settlement	STIR VERY WELL BEFORE AND DURING USE or the product may dry with a satin finish.
Shelf-life/Storage	Many years if stored in original tightly closed container in normal conditions.
Hazards	Keep out of reach of children. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. A full Safety Data Sheet is available upon request or on Rustins Web site.
Clean-Up	Remove excess product from brushes before cleaning. Clean brushes whilst wet with water. Hard brushes can be cleaned with Rustin's Brush Restorer .
Sizes	
	-