

February 2018

PRODUCT DATA SHEET

| | |
|---------------------------|--|
| Product | Quick Drying White Satin Paint |
| Type | A water-based hard wearing satin white paint for interior and exterior use. |
| Intended Use | For use on bare wood, hardboard, MDF, plaster, brickwork and cement. For interior and exterior use. |
| Special Features | Quick drying. Excellent covering power. Low odour. Clean brushes in water. |
| Preparation | Surfaces to be coated must be clean, dry and free from wax, grease and contaminants. If already painted, remove flaking paint by scraping or with Rustin's Strypit Paint and Varnish Stripper . If applying to metal, remove any rust with a scraper or with Rustin's Rust Remover and apply one coat of Rustin's Red Oxide Metal Primer . If applying to bare wood apply, a coat of Rustin's Quick Dry Primer and Undercoat . |
| Application | Stir well before use. Apply liberally and evenly with a synthetic fibre brush. A short haired varnish roller can be used but it is best applied by brush. |
| Coats | 3 coats are recommended and 2 coats on previously painted surfaces. |
| Drying Time | Touch dry within 30 minutes, depending on temperature and humidity. |
| Re-coating Time | Re-coating Time 2 hours minimum, depending on temperature and humidity. |
| Application Temp. | Ideally 15-25° C. Do not use below 10°C or in conditions of high humidity. |
| Coverage | Approximately 13 sq.m per litre per 1 coat, depending on the absorbency of the surface. |
| Maintenance | Keep surface clean with mild detergent and warm water, Reapply when necessary. |
| Compatibility | All types of paint may be applied over this product, such as Rustin's White Gloss Paint and Rustin's Quick-Drying Radiator Enamel . Not for use as a metal primer. Metals must be primed using Rustin's Red Oxide Metal Primer . |
| Settlement | STIR WELL BEFORE USE . Ensure any sediment is thoroughly mixed in. |
| Shelf-life/Storage | Many years in a cool, dry place if stored in original, tightly closed container. Do not store below 5° C. Protect from frost and extremes of temperature. |
| Hazards | Non-flammable. Avoid contact with eyes and skin. Eyes should be rinsed immediately contact occurs with plenty of water. Seek medical attention. Skin should be washed immediately after contact with plenty of soap and water or a proprietary skin cleanser. Use only in well ventilated areas. Keep container tightly closed and out of reach of |
| Clean-Up | Clean brushes and hands immediately after use with water. If dried on, clean equipment and brushes with Rustin's Brush Restorer . |
| Sizes | 125ml 500ml 1 L |