

March 2018

PRODUCT DATA SHEET

Product	Galvanised Primer
Type	Based on high quality water-borne cross linking acrylic resin.
Intended Use	A protective primer for galvanised metal, for bare metal and cast iron.
Special Features	Low odour, low VOC and quick drying. For interior and exterior use. May be over coated with oil-based and water based top coats.
Preparation	The surface must be clean and free from grease and wax.
Application	Stir well before use until there is no sediment on the bottom of the tin. Apply liberally with a synthetic fibre bristle brush to clean bare metal. One coat will provide adequate coverage but 2 coats are recommended for improved durability.
Coats	1 -2 coats.
Drying Time	The paint will touch dry in approximately 30 mins depending upon temperature and humidity.
Re-coating Time	Re-coat after two hours.
Application Temp.	Ideally 15-25°C. Do not use below 10°C, or in conditions of high humidity.
Coverage	13 sq metres/litre per coat.
Maintenance	N/A
Compatibility	Designed to be applied to bare metal and to be top coated with most types of oil and water based top coats.
Settlement	STIR WELL BEFORE USE.
Shelf-life/Storage	A very long time if stored in a cool dry place with the lid firmly secured. Do not store below 10 C and protect from frost.
Hazards	Harmful if swallowed. Keep out of reach of children. Rinse splashes from skin and eyes with clean water. A full Safety Data Sheet is available upon request or on www.rustins.co.uk
Clean-Up	Clean the brushes immediately with water. Hard brushes can be cleaned with Rustins Brush Restorer.
Sizes	250ml 500ml 1 L